

Exhaust nozzles Abgastrichter



GB

Gram exhaust nozzles are available for all car brands standard and special. Design in steel and steel coated with temperature resistant rubber.

D

Gram Abgastrichter werden für alle Auto-Marken Standard und Spezial geliefert. Ausführung in Stahl und Stahl bekleidet mit temperaturbeständigem Gummi.

Picture	Type	Car type	MOT test point	Single	Double	Grip clamp	Damper	Pneumatic	With hand pump	Spring clamp	Nozzle size	ø hose	Order no.
	Conne- ction piece for exhaust emissions type MO	C		X						X	 ø76mm	76	06 257 000
		C		X						X	 ø100mm	100	06 259 000
		C		X						X	 ø125mm	125	06 260 000
		C		X						X	 ø150mm	150	06 261 000
	P-100-50	C	X	X							 ø100mm	50	08 669 100
	P-100-76	C	X	X								76	08 670 000
	P-100-100	C	X	X								100	08 670 100
	V	T		X							 ø150mm	75	08 615 100
		T		X								100	08 615 200
		T		X								125	08 616 300
		T		X								150	08 616 400
	MOG	C	X	X		X	X				 ø125mm	76	06 660 000
		C	X	X		X	X					100	06 661 000
		T	X	X		X	X				 ø150mm	125	06 662 000
		T	X	X		X	X					150	06 663 000
		T	X	X		X	X				 ø200mm	150	06 665 000
		T	X	X		X	X					200	06 666 000
Additional payment for exhaust nozzle type MOG made in steel												06 667 000	
Additional payment for exhaust nozzles type MOG in stainless steel (AISI 304), excl. grip clamp												06 667 500	




Recht auf Änderungen bleibt vorbehalten. / Data is subject to alterations.

Rev. 12.16

C=car T=truck

Exhaust nozzles

Abgastrichter

Picture	Type	Car type	MOT test point	Single	Double	Grip clamp	Damper	Pneumatic	With hand pump	Nozzle size	ø hose	Order no.
	DOG	C	X		X	X	X				76	06 670 000
		C	X		X	X	X				100	06 671 000
		C	X		X	X	X				125	06 673 000
	DT	C			X			X	X		76	08 620 500
		C			X			X	X		100	08 620 600
		C			X			X	X		125	08 620 700
	DL	C			X			X			100	08 612 600
 (Delivery standard without damper)	PL	C		X				X			76	08 611 400
		C		X				X			100	08 611 500
		C		X				X			125	08 611 600
 (Delivery standard without damper)	VLL	T		X				X			100	08 611 700
		T		X				X			125	08 611 800
		T		X				X			150	08 611 900
		T		X				X			125	08 618 100
		T		X				X			150	08 618 200
	Loose hand pump for pneumatic exhaust nozzle, inclusive pressure valve and 100mm hose											08 625 500
	Gram vertical exhaust nozzle	T		X							125	06 679 000
		T		X							150	06 680 000


Recht auf Änderungen bleibt vorbehalten. / Data is subject to alterations.

Rev. 12.16

C=car T=truck

Exhaust nozzles

Abgastrichter

Picture	Type	Car type	Single	Double	Height adjustable	Nozzle size	ø hose	Order no.
	Mobile nozzle for exhaust extraction from trucks	T	X			Special reduction from ø150mm	76	06 243 000
		T	X			Special reduction from ø150mm	100	06 243 100
		T	X			Special reduction from ø150mm	125	06 243 200
		T	X		100 - 800	 ø150mm	150	06 242 000

Picture	Type	Description	Material	Dimension	Order no.
	Hose support bracket	Bracket to support hose to avoid break and wear of hose in connection with suspension in e.g. balancer	Made of neoprene with one strengthening layer	 ø76mm	06 690 000
				 ø100mm	06 691 000
				 ø125mm	06 692 000
				 ø150mm	06 693 000
				 ø200mm	06 695 000
	Wall hose bracket	For storage of hose, e.g. on the wall	Made in powder enamelled steel	 ø76 - 100mm	06 624 000
				 ø125 - 150mm	06 625 000

C=car T=truck

Twin exhaust nozzle for motor cycles

Doppeltrichter für Motorräder



GB

- Free movement at height and width adjustment
- Delivered with welded-on weight block 3kg beneath platform for stability
- 2 pcs. exhaust nozzles type P100-100
- Platform with wheels for large stability
- 2 pcs. 500mm hose type S3B ø100mm
- 1 pcs. Y-pipe 3x100mm nipple
- Order no.: 06 150 000

D

- Freie Bewegung bei Höhen- und Breitenjustierung
- Wird mit aufgeschweißtem Gewichtsklotz 3kg auf Unterseite von Plattform für Stabilität geliefert
- 2 Stck. Abgastrichter Typ P100-100
- Plattform mit Rädern für große Stabilität
- 2 Stck. 500mm Schlauch Typ S3B ø100mm
- 1 Stck. Y-Rohr 3x100mm Nippel
- Bestell-Nr.: 06 150 000